BRAMPTON TECHNOLOGY, LTD

55 Maselli Rd. Newington, CT 06111 Ph. 860-667-7689 Fx. 860-666-1425 www.bramptontechnology.com

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PRO-FIX 20/20 PART A 8-20-12

SECTION 2- HAZARDOUS INGREDIENTS / DENSITY

HAZARDOUS COMPONENT(S) (chemical & common name(s) **OSHA** ACGIH Other Exposure %

PEL TLV Limits

Epoxy Resin NONE NONE NONE 80-90 **Rubber Modifiers** NONE NONE NONE 10-20 **Inert Fillers** NONE NONE NONE 2-5

This product does not contain any hazardous chemicals as defined by the OSHA Hazard Communications standard

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Vapor Pressure N/A **Boiling Point:** Decomposes Specific Gravity 1.15

(mm Hg); Solid before boiling (H2O - 1):

Solubility in Water Negligible Reactivity in Water NONE Vapor Density:

Melting Point: Soften and Melts Appearance Opaque, no and Odor noticeable odor

over 140 degree F

SECTION 4 - FIRE & EXPLOSIVE DATA

UEL Flash Over Method Flammable Limits in LEL

Point: 200 deg. F Closed Cup Air % by volume not determined Not Determined

Auto-Ignition Temperature: Over 500 deg. F Extinguisher Media: Foam CO2, Dry Chemical

Special Fire Fighting Procedure: USE SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: Exothermic, Decomposes

SECTION 5 - PHYSICAL HAZARDS (REACTIVITY DATA)

Stability: Stable Conditions to avoid: None Incompatibility (material to avoid); Strong acids, alkalis, amines

Hazardous Decomposition Products: Oxides of carbon and nitrogen, aldehydes and other organics.

Hazardous Polymerizations: Not available Conditions to avoid: Do not expose to fire, flame or excessive heat

SECTION 6 - HEALTH HAZARDS

Hazard Possible minor skin irritation may result from excessive contact with adhesive.

Medical Conditions Generally Aggravated by Exposure:

Chemical listed as Carcinogen National Toxicology Program NO I.A.R.C. Monographs NO OSHA: NO

First Aid: Routes of Entry Inhalation: N/A Eyes: Flush with water and seek medical attention. Skin: Wash skin with soap and water, remove contaminated clothing and wash. Ingestion: Not a probable route

of entry.

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES

Precautions to be Taken in Handling and Storage: Store at 60 deg F for long shelf life. Other Precautions None

Steps to be Taken in Case Material is Released or Spilled: Contain with speedy-dry and containerize.

Waste Disposal Methods: Bury as solid waste in an approved landfill or incinerate in accordance with regulations.

SECTION 8 – SPECIAL PROTECTION INFORMATION / CONTROL MEASURES

Respiratory Protection: Not normally necessary. Eye protection always Ventilation: Mechanical suggested

Protective Gloves: Cotton, rubber Other Protective Clothing or Equipment: Clean long sleeve and leg clothing

Work / Hygiene Practices: Normal good industrial

BRAMPTON TECHNOLOGY, LTD

55 Maselli Rd. Newington, CT 06111 Ph. 860-667-7689 Fx. 860-666-1425 www.bramptontechnology.com

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PRO-FIX 20/20 PART B 8-20-12

SECTION 2- HAZARDOUS INGREDIENTS / DENSITY

HAZARDOUS COMPONENT(S) (chemical & common name(s) OSHA ACGIH Other Exposure %

PEL TLV Limits

Alkylamine NONE NONE NONE 80-90 Substituted Aminophenol NONE NONE NONE 10-20

This product does not contain any hazardous chemicals as defined by the OSHA Hazard Communications standard

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point: No Specific Gravity .96 Vapor Pressure <1%

Data (H2O – 1): (mm Hg);

Vapor Density: N/A Solubility in Water Slight Reactivity in Water No Data

Appearance Amber Melting Point: No Data

and Odor Ammoniacal Irritating

SECTION 4 – FIRE & EXPLOSIVE DATA

Flash Over Method Closed Flammable Limits in LEL Not UEL Not

Point: 200 deg. F Used: Cup Air % by volume Lower: Determined Upper: Determined

Auto-Ignition Temperature: No Data Extinguisher Media: Foam CO2, Dry Chemical

Special Fire Fighting Procedure: USE SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: May generate irritating combustions products. Sudden reaction and Fire may result if product is

mixed with an oxidizing agent

SECTION 5 – PHYSICAL HAZARDS (REACTIVITY DATA)

Stability: Stable Conditions to avoid: None

Incompatibility (material to avoid); Oxidizing Agents, cleaning solutions, such as chromerge (sulfuric acid/dichromate)

Hazardous Decomposition Products: Oxides of carbon and nitrogen, aldehydes and other organics.

Hazardous Polymerizations: Will not occur by itself, but masses combined with epoxy resin cause irreversible

polymerization with heat build up. Conditions to avoid: Do not expose to fire, flame or excessive heat

SECTION 6 – HEALTH HAZARDS

Hazard Possible minor skin irritation may result from excessive contact with adhesive.

Medical Conditions Generally Aggravated by Exposure: Sensitive skin, allergies

Chemical listed as Carcinogen National Toxicology Program NO I.A.R.C. Monographs NO OSHA: NO

First Aid: Routes of Entry Inhalation: N/A Eyes: Flush with water and seek medical attention. Skin: Wash skin with soap and water, remove contaminated clothing and wash. Ingestion: Not a probable route

of entry.

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL / LEAK PROCEDURES

Precautions to be Taken in Handling and Storage: Store at 0 deg F for long shelf life. Keep away from oxidizers

Other Precautions: Emergency shower and eye wash station should be readily accessible.

Steps to be Taken in Case Material is Released or Spilled: Contain with speedy-dry and containerize.

Waste Disposal Methods: Bury as solid waste in an approved landfill or incinerate in accordance with regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION / CONTROL MEASURES

Respiratory Protection: Not normally necessary. Eye protection always Ventilation: Mechanical suggested

Protective Gloves: Cotton, rubber Other Protective Clothing or Equipment: Clean long sleeve and leg clothing

Work / Hygiene Practices: Normal good industrial